

Disentangled Contrastive Learning for Social Recommendation

Jiahao Wu

The Hong Kong Polytechnic
University
Hong Kong, China
Southern University of Science and
Technology
Shenzhen, Guangdong, China
jiahao.wu@connect.polyu.hk

Wenqi Fan*

The Hong Kong Polytechnic
University
Hong Kong, China
wenqifan03@gmail.com

Jingfan Chen

The Hong Kong Polytechnic
University
Hong Kong, China
Centre for Artificial Intelligence and
Robotics (HKISI_CAS)
Hong Kong, China
jingfan.chen@connect.polyu.hk

Shengcai Liu

Southern University of Science and
Technology
Shenzhen, Guangdong, China
liusc3@sustech.edu.cn

Qing Li

The Hong Kong Polytechnic
University
Hong Kong, China
csqli@comp.polyu.edu.hk

Ke Tang

Southern University of Science and
Technology
Shenzhen, Guangdong, China
tangk3@sustech.edu.cn

ABSTRACT

Social recommendations utilize social relations to enhance the representation learning for recommendations. Most social recommendation models unify user representations for the user-item interactions (collaborative domain) and social relations (social domain). However, such an approach may fail to model the users' heterogeneous behavior patterns in two domains, impairing the expressiveness of user representations. In this work, to address such limitation, we propose a novel Disentangled contrastive learning framework for social Recommendations (**DeRec**). More specifically, we propose to learn disentangled users' representations from the item and social domains. Moreover, disentangled contrastive learning is designed to perform knowledge transfer between disentangled users' representations for social recommendations. Comprehensive experiments on various real-world datasets demonstrate the superiority of our proposed model.

CCS CONCEPTS

• **Information systems** → **Recommender systems, Social recommendation**; • **Self-supervised learning**;

KEYWORDS

Social Recommendations, Self-Supervised Learning, Disentangled Learning, Collaborative Learning.

ACM Reference Format:

Jiahao Wu, Wenqi Fan, Jingfan Chen, Shengcai Liu, Qing Li, and Ke Tang. 2022. Disentangled Contrastive Learning for Social Recommendation. In

*Corresponding Author.

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than ACM must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from [permissions@acm.org](https://permissions.acm.org).
CIKM '22, October 17–21, 2022, Atlanta, GA, USA

© 2022 Association for Computing Machinery.
ACM ISBN 978-1-4503-9236-5/22/10...\$15.00
<https://doi.org/10.1145/3511808.3557583>

Proceedings of the 31st ACM International Conference on Information and Knowledge Management (CIKM '22), October 17–21, 2022, Atlanta, GA, USA.
ACM, New York, NY, USA, 7 pages. <https://doi.org/10.1145/3511808.3557583>

1 INTRODUCTION

As suggested by social correlation theories [4], users' preferences are likely to be influenced by those around them. Based on this intuition, a bunch of works have been proposed to utilize the information of social relations in modeling users' preferences for items to enhance recommendation performance in various online platforms (e.g., Facebook, WeChat, LinkedIn, etc.) [7, 15, 30], known as social recommendations [10, 12, 13, 40, 42].

In social recommendation, as shown in Figure 1, users are interacted with different objectives (i.e., items and social friends) with distinct purposes in each domain (i.e., collaborative domain and social domain) [7]. Therefore, the behavior patterns of users in two domains can be heterogeneous. In a real scenario, a user tends to connect with friends of his/her friends but he/she are not likely to purchase the items serving similar functions in a short period of time. However, off-the-shelf manners on modeling users' preferences adopt unified users' representations for user-item interactions and user-user social relationships. For instance, Diffnet++ [42] utilizes a node-level attention layer to fuse the users' representations from social domain and collaborative domain. DSCF [14] uses unified users' representations to capture social information and user-item interaction information. They are insufficient to model users' heterogeneous behavior patterns towards social friends and items in social recommendations, which may undermine the representation learning in each domain.

To address this problem, in this work, we propose to *disentangle* user behaviors into two domains, so as to learn disentangled users' representations in the social recommendations task, instead of the unified users' representations. The main challenge is how to learn such disentangled users' representations in two domains while transferring knowledge from social domain to collaborative domain for social recommendations.

Recently, Self-Supervised Learning (SSL), a prevalent novel learning paradigm, has been proven beneficial to the tasks in a




Figure 1: Users are involved in both collaborative domain and social domain. The behavior patterns of users in two domains are semantically heterogeneous, where a user can have his/her personalized preferences towards items in the collaborative domain while connecting with social friends in the social domain.

wide range of fields [2, 6, 17, 24, 36, 41]. The main idea of SSL is to utilize self-supervision signals from unlabeled data by maximizing the mutual information between different augmented views of the same instance (i.g., user or item) [37], in the representation learning process of which SSL increases the informativeness of those views and enables knowledge transferring between those views [46]. For instance, SGL [39] devises various auxiliary tasks to learn the structure relatedness knowledge between different views and utilize it to supplement supervision signals. MHCN [46] constructs different hyper-graphs and maximizes the mutual information between the users and the hyper-graphs to learn the hierarchical structure information and transfer it into the learned nodes' representations.

Motivated by the advantage of SSL in transferring knowledge, we develop a novel contrastive learning-based framework to solve the aforementioned issue. More specifically, domain disentangling is introduced to disentangle users' behaviors into collaborative domain and social domain. Moreover, we propose disentangled contrastive learning objectives to transfer knowledge from social domain to collaborative domain by maximizing the mutual information between disentangled representations. Notably, while DGCL [24] proposes an implicitly disentangled contrastive learning method to capture multiple aspects of graphs, we explicitly disentangle the data from different domains and propagate the representations of nodes based on independent adjacency matrices. The main contributions of this paper can be summarized as follows:

- We introduce a principled approach to learn users' representations, where disentangled users' representations can be learned to reflect their preferences towards items and social friends in two domains.
- We propose a novel Disentangled contrastive learning framework for social Recommendations (**DcRec**), which can harness the power of contrastive learning to transfer knowledge from social domain to collaborative domain.
- We conduct comprehensive experiments on various real-world datasets to show the superiority of the proposed model and study the effectiveness of each module.

2 METHODOLOGY

We first introduce definitions and notations used in this paper. We utilize \mathcal{U} to stand for the user set and \mathcal{I} to stand for the item set. Let $m = |\mathcal{U}|$ defines the number of users and $n = |\mathcal{I}|$ denotes the number of items. Then, we denote the user-item interactions matrix in the collaborative domain by $\mathbf{A}_I \in \mathbb{R}^{m \times n}$ and social relations matrix in the social domain by $\mathbf{A}_S \in \mathbb{R}^{m \times m}$. In addition, we use dense vectors to represent users and items (i.e., embeddings), where $\mathbf{P}_S \in \mathbb{R}^{m \times d}$ and $\mathbf{P}_I \in \mathbb{R}^{m \times d}$ denote users' embeddings with d dimension in social domain and collaborative domain, respectively. $\mathbf{Q}_I \in \mathbb{R}^{n \times d}$ denotes items' embeddings in the collaborative domain.

2.1 An Overview of the Proposed Framework

In this work, we propose a Disentangled contrastive learning framework for social Recommendations (**DcRec**), which follows the general paradigm of self-supervised contrastive learning via maximizing the representation agreement between different views on the same instance [2, 21, 39].

The architecture of the proposed model is shown in Figure 2. More specifically, the proposed architecture consists of three main components: (1) **Domain Disentangling**, which is devised to disentangle the input data into two sub-domains; (2) **Encoder**, where we use different encoders on two domains to learn representations from two different views; (3) **Disentangled Contrastive Learning**, which aims to transfer the knowledge from the social domain into recommendation modeling task by jointly optimizing the disentangled contrastive learning tasks and main recommendation task.

2.2 Domain Disentangling

To mitigate the influence caused by the semantic discrepancy between social domain and collaborative domain, we disentangle the input data into two domains, which will be represented by a user-item interactions matrix \mathbf{A}_I in the collaborative domain and social relations matrix \mathbf{A}_S in the social domain, respectively.

After domain disentanglement, we perform data augmentation to obtain different views for the data in each domain. Since the data in social recommendations can be naturally represented as graph [12], the inputs (i.e., user-item interactions \mathbf{A}_I and social relations \mathbf{A}_S) can be augmented via graph-based data augmentation methods [21, 44], such as *Edge Adding*, *Edge Dropout*, and *Node Dropout*, which can be formulated as follows:

$$\begin{aligned} \mathbf{A}_S^{(1)} &= H_S^{(1)}(\mathbf{A}_S), \mathbf{A}_S^{(2)} = H_S^{(2)}(\mathbf{A}_S), \\ \mathbf{A}_I^{(1)} &= H_I^{(1)}(\mathbf{A}_I), \mathbf{A}_I^{(2)} = H_I^{(2)}(\mathbf{A}_I), \end{aligned}$$

where $H_S^{(\cdot)}$ and $H_I^{(\cdot)}$ denote the independent augmentation functions to generate two views in social domain and collaborative domain, respectively.

2.3 Encoder

To model the user-item interactions and social relations, we utilize encoders to learn representations for users and items in each domain. Furthermore, to ensure semantic consistency while conducting cross-domain contrastive learning between users' representations from two different domains, we also project the users' representations into the same semantic space. Here, we use




Figure 2: The overall architecture of the proposed disentangled contrastive learning for social recommendations (DcRec).

$Rec(\cdot)$ and $F(\cdot)$ to represent the encoder in the item and social domains, respectively. Note that any Collaborative Filtering (CF) based models (e.g., MF [23], NeuMF [19], and LightGCN [18].) can be set as the recommendation encoder $Rec(\cdot)$ in the collaborative domain, and we can set Graph Neural Networks (GNNs) methods [5, 9, 11] as social encoder $F(\cdot)$.

2.3.1 Recommendation Encoder in Collaborative Domain.

The collaborative domain encoder aims to learn the representations of users and items by encoding the user-item interactions (i.e., $A_I^{(1)}$ and $A_I^{(2)}$) from two augmented views. In practice, a simple yet effective GNN-based recommendation model LightGCN [18] is used as collaborative domain encoder $Rec(\cdot)$ and we can obtain users' and items' representations from two views (i.e., $A_I^{(1)}$ and $A_I^{(2)}$) as:

$$\mathbf{U}_I^{(1)}, \mathbf{V}_I^{(1)} = \text{Rec}(A_I^{(1)}; \Theta_I), \mathbf{U}_I^{(2)}, \mathbf{V}_I^{(2)} = \text{Rec}(A_I^{(2)}; \Theta_I), \quad (1)$$

where Θ_I is the parameter of the recommendation encoder. $\mathbf{U}_I^{(1)} \in \mathbb{R}^{m \times d}$, $\mathbf{U}_I^{(2)} \in \mathbb{R}^{m \times d}$, $\mathbf{V}_I^{(1)} \in \mathbb{R}^{n \times d}$ and $\mathbf{V}_I^{(2)} \in \mathbb{R}^{n \times d}$ are learned representations of users and items from two views for contrastive learning. Furthermore, we also use this encoder $Rec(\cdot)$ to train our primary task via BPR loss [18] (Eq. 8) and learn final users and items representations (i.e., $\mathbf{U} \in \mathbb{R}^{m \times d}$ and $\mathbf{V} \in \mathbb{R}^{n \times d}$) on user-item interactions (i.e., A_I) for making predictions as follows:

$$\mathbf{U}, \mathbf{V} = \text{Rec}(A_I; \Theta_I).$$

2.3.2 GNNs Encoder in Social Domain. The encoder in social domain aims at learning users' representations by capturing social relations among users. Here, due to the excellent expressiveness of GNNs in modeling graph structural data [12], we adopt a general GNNs method [22] as an encoder (i.e., $F(\cdot)$) to obtain user representations in social domain as follows:

$$\mathbf{U}_S^{(1)} = F(A_S^{(1)}; \Theta_S), \mathbf{U}_S^{(2)} = F(A_S^{(2)}; \Theta_S), \quad (2)$$

where Θ_S denotes the parameters of GNNs encoder in the social domain. $\mathbf{U}_S^{(1)} \in \mathbb{R}^{m \times d}$ and $\mathbf{U}_S^{(2)} \in \mathbb{R}^{m \times d}$ are learned representations of users from two views for contrastive learning in social domain.

2.3.3 Semantic Projection. Since users' representations learned from collaborative domain and social domain are semantically heterogeneous, we propose to project them into the same semantic space. Specifically, in social domain, we adopt Multilayer Perceptrons (MLPs) to perform such projection on users' representations as: $\tilde{\mathbf{U}}_S^{(1)} = \text{MLP}(\mathbf{U}_S^{(1)}; \theta_S)$, $\tilde{\mathbf{U}}_S^{(2)} = \text{MLP}(\mathbf{U}_S^{(2)}; \theta_S)$, where θ_S is the

set of MLPs' parameters in the social domain. Analogously, we can obtain users' representations $\tilde{\mathbf{U}}_I^{(1)}$ and $\tilde{\mathbf{U}}_I^{(2)}$ in the collaborative domain via MLP with parameters θ_I .

2.4 Disentangled Contrastive Learning

Disentangled contrastive learning consists of cross-domain contrastive learning and domain-specific contrastive learning. We devise cross-domain contrastive learning so as to transfer the knowledge from social domain to collaborative domain. In order to take advantage of self-supervision signals from unlabeled data under contrastive learning paradigm [2, 21, 39], we introduce domain-specific loss to maximize the representation agreement between different views on the same instance in each domain.

2.4.1 Cross-domain Contrastive Learning Loss. In order to transfer the knowledge from social domain to collaborative domain, we design cross-domain contrastive learning loss based on the projected users' representations (i.e., $\tilde{\mathbf{U}}_S^{(1)}, \tilde{\mathbf{U}}_S^{(2)}, \tilde{\mathbf{U}}_I^{(1)}, \tilde{\mathbf{U}}_I^{(2)}$) as follows:

$$\mathcal{L}_C = L(\tilde{\mathbf{U}}_S^{(1)}, \tilde{\mathbf{U}}_I^{(1)}) + L(\tilde{\mathbf{U}}_S^{(1)}, \tilde{\mathbf{U}}_I^{(2)}) + L(\tilde{\mathbf{U}}_S^{(2)}, \tilde{\mathbf{U}}_I^{(1)}) + L(\tilde{\mathbf{U}}_S^{(2)}, \tilde{\mathbf{U}}_I^{(2)}), \quad (3)$$

where $L(\cdot, \cdot)$ denotes a common contrastive learning loss which distinguishes the representations of the same users in these different views from other users' representations [26, 39, 50], where $L(\tilde{\mathbf{U}}_S^{(1)}, \tilde{\mathbf{U}}_I^{(1)})$, $L(\tilde{\mathbf{U}}_S^{(1)}, \tilde{\mathbf{U}}_I^{(2)})$, $L(\tilde{\mathbf{U}}_S^{(2)}, \tilde{\mathbf{U}}_I^{(1)})$ and $L(\tilde{\mathbf{U}}_S^{(2)}, \tilde{\mathbf{U}}_I^{(2)})$ are denoted by L^2 , L^3 , L^1 and L^4 in Figure 2, respectively.

Due to symmetric property in two contrasted views, a common contrastive learning loss $L(\cdot, \cdot)$ can be formally given by:

$$L(\mathbf{Z}^{(1)}, \mathbf{Z}^{(2)}) = \frac{1}{2w} \sum_{j=1}^w \left[\text{loss}(\mathbf{z}_j^{(1)}, \mathbf{z}_j^{(2)}) + \text{loss}(\mathbf{z}_j^{(2)}, \mathbf{z}_j^{(1)}) \right], \quad (4)$$

where $\mathbf{Z}^{(1)} \in \mathbb{R}^{w \times d}$ and $\mathbf{Z}^{(2)} \in \mathbb{R}^{w \times d}$ are instances' representations in two different views, and $\mathbf{z}_j^{(1)}$ and $\mathbf{z}_j^{(2)}$ are corresponding representations of u -th instance (i.e., users and items) in two views and $w \in \{m, n\}$. Inspired by the design in [50], the $\text{loss}(\mathbf{z}_j^{(1)}, \mathbf{z}_j^{(2)})$ can be formulated as:

$$\text{loss}(\mathbf{z}_j^{(1)}, \mathbf{z}_j^{(2)}) = -\log \frac{e^{\Psi(\mathbf{z}_j^{(1)}, \mathbf{z}_j^{(2)})}}{e^{\Psi(\mathbf{z}_j^{(1)}, \mathbf{z}_j^{(2)})} + \sum_{v \in \{1,2\}} \sum_{k \neq j} e^{\Psi(\mathbf{z}_j^{(1)}, \mathbf{z}_k^{(v)})}}, \quad (5)$$

where $\Psi(\mathbf{z}_1, \mathbf{z}_2) = s(\mathbf{z}_1, \mathbf{z}_2)/\tau$, measuring the cosine similarity between two representations, and τ is the temperature parameter.

3.4.2 Domain-specific Contrastive Learning Loss. To enhance the expressiveness of the learned representations for each instance in each domain, we design domain-specific contrastive learning loss in the two domains:

$$\text{Collaborative Domain: } \mathcal{L}_I = L(\mathbf{U}_I^{(1)}, \mathbf{U}_I^{(2)}) + L(\mathbf{V}_I^{(1)}, \mathbf{V}_I^{(2)}), \quad (6)$$

$$\text{Social Domain: } \mathcal{L}_S = L(\tilde{\mathbf{U}}_S^{(1)}, \tilde{\mathbf{U}}_S^{(2)}), \quad (7)$$

where \mathcal{L}_S and \mathcal{L}_I are domain-specific contrastive learning losses for the social domain and collaborative domain, respectively. Note that in practice, the projected representations in the social domain are used to conduct the domain-specific contrastive learning due to the promising results in our experiments.

2.5 Model Optimization

2.5.1 Primary Recommendation Task. Given the learned representation \mathbf{u}_u and \mathbf{v}_i for user u and item i , we adopt a widely used inner product to predict the score for measuring how likely the user u will interact with item i as: $\hat{y}_{ui} = \mathbf{u}_u^T \mathbf{v}_i$.

To optimize the primary recommendation task, we choose Bayesian Personalized Ranking (BPR) loss [34], formulated as:

$$\mathcal{L}_{main} = \sum_{(u,i,j) \in \mathcal{O}} -\log \sigma(\hat{y}_{ui} - \hat{y}_{uj}), \quad (8)$$

where $\mathcal{O} = \{(u, i, j) | (u, i) \in \mathcal{O}^+, (u, j) \in \mathcal{O}^-\}$. Here, \mathcal{O}^+ is the set of observed interactions and \mathcal{O}^- is the set of unobserved ones.

2.5.2 Joint Training. To improve the recommendation performance by our proposed model with disentangled contrastive learning, we adopt a joint training strategy to optimize both the recommendation loss and contrastive learning loss:

$$\mathcal{L} = \mathcal{L}_{main} + \lambda_1(\mathcal{L}_I + \mathcal{L}_S) + \lambda_2 \mathcal{L}_C + \lambda_3 \|\zeta\|_2,$$

where λ_1 , λ_2 , and λ_3 are hyperparameters to balance the contributions of various contrastive learning losses and regularization.

3 EXPERIMENTS

Due to the space limitation, the detailed experimental settings, evaluation metrics, baseline and implementations could be found in Appendix Section.

3.1 Experiment Results

3.1.1 Overall Performance Comparison. In this part, we verify the effectiveness of the proposed model DcRec for recommendation performance. The overall comparisons between our model with other methods are given in Table 1. The baselines used for comparisons range from classical MF-based models, GNNs-based models to recent SSL enhanced models. According to the results, we can draw the following findings:

- The proposed DcRec achieves the best recommendations performance under all evaluation metrics on Dianping and Ciao datasets, achieving promising improvement over the strongest baselines that are marked with underlines. Compared to SSL-enhanced social recommendation baselines, our method incorporates advanced components to learn representations from social and collaborative domains by disentangled contrastive learning.
- In most cases, SSL-enhanced methods outperform those methods without SSL on Dianping and Ciao datasets over various metrics.

Table 1: Overall Performance Comparison

Dataset	Dianping			Ciao		
	Metrics	NDCG	Recall	Precision	NDCG	Recall
BPR [34]	0.0188	0.0189	0.0145	0.0226	0.0155	0.0177
SBPR [47]	0.0162	0.0203	0.0217	0.0284	0.0191	0.0223
SoRec [31]	0.0149	0.0149	0.0111	0.0220	0.0147	0.0165
SocialMF [20]	0.0144	0.0148	0.0109	0.0218	0.0154	0.0166
Diffnet [42]	0.0241	0.0242	0.0181	0.0280	0.0182	0.0213
NGCF [38]	0.0287	0.0289	0.0221	0.0232	0.0157	0.0183
LightGCN [18]	0.0396	0.0384	0.0292	0.0326	<u>0.0224</u>	0.0253
LightGCN+Social	0.0392	0.0381	0.0289	0.0326	0.0220	0.0254
SGL [39]	<u>0.0421</u>	<u>0.0414</u>	<u>0.0310</u>	<u>0.0340</u>	0.0223	<u>0.0266</u>
SGL+Social	0.0405	0.0402	0.0299	0.0334	0.0221	<u>0.0266</u>
MHCN [46]	0.0398	0.0399	0.0296	0.0315	0.0218	0.0252
SEPT [45]	0.0378	0.0371	0.0286	0.0313	0.0212	0.0250
DcRec(w/o MLP)	0.0417	0.0409	0.0307	0.0338	0.0217	0.0263
DcRec	0.0443	0.0441	0.0327	0.0366	0.0243	0.0280
%Improv.	5.31%	6.63%	5.29%	6.46%	8.39%	5.32%

Table 2: Ablation study of λ_1 and λ_2 on dataset Ciao

✓		Metrics			✓		Metrics		
λ_1	λ_2	NDCG	Recall	Precision	λ_1	λ_2	NDCG	Recall	Precision
0	0.01	0.03488	0.02436	0.02668	0.01	0	0.03617	0.02394	0.02794
0.001	0.01	0.03498	0.02416	0.02662	0.01	0.001	0.03657	0.02430	0.02795
0.01	0.01	0.03629	0.02405	0.02773	0.01	0.01	0.03629	0.02405	0.02773
0.1	0.01	0.02735	0.01760	0.02191	0.01	0.1	0.03635	0.02412	0.02803
1	0.01	0.00814	0.00513	0.00681	0.01	1	0.03618	0.02398	0.02803
10	0.01	0.00103	0.00088	0.00075	0.01	10	0.03626	0.02419	0.02803

This observation demonstrates the effectiveness of SSL for recommendations, which empirically shows the necessity of designing the domain-specific contrastive learning part.

3.1.2 Ablation Study on MLP. As shown in Table 1, without the MLP for semantic projection, the performance degrades on all metrics for two datasets. This empirically verifies the effectiveness of the design of semantic projection.

3.1.3 Sensitivity Study on λ_1 and λ_2 . As shown in Table 2, we present the performance of DcRec with different values of λ_1 and λ_2 . From the left part, studying the λ_1 , we can find that setting a large value could lead to great drop on performance. We argue that this is because a large weight for domain-specific contrastive learning can lead the optimization towards instance discrimination (the objective of SSL) instead of the recommendation objective. From the right part, we found a similar phenomenon, but the best value for λ_2 is much smaller. We justify that this is because the proper amount of social information is beneficial to recommendation task but too much is harmful.

4 CONCLUSION

To model the heterogeneous behavior patterns of users in social domain and item domain, we proposed a disentangled contrastive learning framework for social recommendations, which disentangles two domains and learns users' representations in each domain, respectively. Furthermore, we devised cross-domain contrastive learning to transfer knowledge from the social domain to the item domain, so as to enhance the recommendation performance. The extensive experiments conducted on two real-world datasets demonstrate the effectiveness of our proposed model and its superiority over previous works.

ACKNOWLEDGMENTS

This work was supported in part by the Guangdong Provincial Key Laboratory under Grant 2020B121201001, in part by the Program for Guangdong Introducing Innovative and Entrepreneurial Teams under Grant 2017ZT07X386, and in part by the Shenzhen Peacock Plan under Grant KQTD2016112514355531. Qing LI, Wenqi FAN, and Jingfan CHEN are partly supported by NSFC (project no. 62102335), an internal research fund from The Hong Kong Polytechnic University (project no. P0036200 and P0042693), a General Research Fund from the Hong Kong Research Grants Council (Project No.: PolyU 15200021 and PolyU 15207322).

REFERENCES

- [1] Jingfan Chen, Wenqi Fan, Guanghui Zhu, Xiangyu Zhao, Chunfeng Yuan, Qing Li, and Yihua Huang. 2022. Knowledge-enhanced Black-box Attacks for Recommendations. In *Proceedings of the 28th ACM SIGKDD Conference on Knowledge Discovery and Data Mining*. 108–117.
- [2] Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey E. Hinton. 2020. A simple framework for contrastive learning of visual representations. In *Proceedings of the 37th International Conference on Machine Learning*.
- [3] Ting Chen, Simon Kornblith, Kevin Swersky, Mohammad Norouzi, and Geoffrey E. Hinton. 2020. Big self-supervised models are strong semi-supervised learners. In *Proceedings of the 33th Advances in Neural Information Processing Systems, NeurIPS'20*. Curran Associates, Inc., Virtual Event, 22243–22255.
- [4] Robert B Cialdini and Noah J Goldstein. 2004. Social influence: Compliance and conformity. *Annual Review of Psychology* 55 (2004), 591–621.
- [5] Tyler Derr, Yao Ma, Wenqi Fan, Xiaorui Liu, Charu Aggarwal, and Jiliang Tang. 2020. Epidemic graph convolutional network. In *Proceedings of the 13th International Conference on Web Search and Data Mining (WSDM)*. 160–168.
- [6] Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2019. BERT: Pre-training of Deep Bidirectional Transformers for Language Understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, NAACL '19*. Association for Computational Linguistics, Minnesota, 4171–4186.
- [7] Wenqi Fan, Tyler Derr, Yao Ma, Jianping Wang, Jiliang Tang, and Qing Li. 2019. Deep adversarial social recommendation. In *Proceedings of the 28th International Joint Conference on Artificial Intelligence*. China.
- [8] Wenqi Fan, Tyler Derr, Xiangyu Zhao, Yao Ma, Hui Liu, Jianping Wang, Jiliang Tang, and Qing Li. 2021. Attacking black-box recommendations via copying cross-domain user profiles. In *2021 IEEE 37th International Conference on Data Engineering (ICDE)*. IEEE, 1583–1594.
- [9] Wenqi Fan, Wei Jin, Xiaorui Liu, Han Xu, Xianfeng Tang, Suhang Wang, Qing Li, Jiliang Tang, Jianping Wang, and Charu Aggarwal. 2021. Jointly attacking graph neural network and its explanations. *arXiv preprint arXiv:2108.03388* (2021).
- [10] Wenqi Fan, Qing Li, and Min Cheng. 2018. Deep modeling of social relations for recommendation. In *Proceedings of the AAAI Conference on Artificial Intelligence*.
- [11] Wenqi Fan, Xiaorui Liu, Wei Jin, Xiangyu Zhao, Jiliang Tang, and Qing Li. 2022. Graph Trend Filtering Networks for Recommendation. In *Proceedings of the 45th International ACM SIGIR Conference on Research and Development in Information Retrieval*. 112–121.
- [12] Wenqi Fan, Yao Ma, Qing Li, Yuan He, Eric Zhao, Jiliang Tang, and Dawei Yin. 2019. Graph neural networks for social recommendation. In *Proceedings of the 30th The Web Conference, WWW'19*. ACM, CA, 417–426.
- [13] Wenqi Fan, Yao Ma, Qing Li, Jianping Wang, Guoyong Cai, Jiliang Tang, and Dawei Yin. 2020. A graph neural network framework for social recommendations. *IEEE Transactions on Knowledge and Data Engineering* (2020).
- [14] Wenqi Fan, Yao Ma, Dawei Yin, Jianping Wang, Jiliang Tang, and Qing Li. 2019. Deep Social Collaborative Filtering. In *Proceedings of the 13th ACM Conference on Recommender Systems*. ACM, Denmark, 305–313.
- [15] Guibing Guo, Jie Zhang, and Neil Yorke-Smith. 2015. TrustSVD: collaborative filtering with both the explicit and implicit influence of user trust and of Item Ratings. In *Proceedings of the 29th AAAI Conference on Artificial Intelligence*.
- [16] Bowen Hao, Jing Zhang, Hongzhi Yin, Cuiping Li, and Hong Chen. 2021. Pre-training graph neural networks for cold-start users and items representation. In *Proceedings of the 14th ACM International Conference on Web Search and Data Mining*. ACM.
- [17] Kaiming He, Haoqi Fan, Yuxin Wu, Saining Xie, and Ross Girshick. 2020. Momentum contrast for unsupervised visual representation learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*.
- [18] Xiangnan He, Kuan Deng, Xiang Wang, Yan Li, Yongdong Zhang, and Meng Wang. 2020. Lightgcn: Simplifying and powering graph convolution network for recommendation. In *Proceedings of the 43rd International ACM SIGIR conference on research and development in Information Retrieval*. ACM, China.
- [19] Xiangnan He, Lizi Liao, Hanwang Zhang, Liqiang Nie, Xia Hu, and Tat-Seng Chua. 2017. Neural Collaborative Filtering. In *WWW*.
- [20] Mohsen Jamali and Martin Ester. 2010. A matrix factorization technique with trust propagation for recommendation in social networks. In *RecSys*. ACM.
- [21] Wei Jin, Tyler Derr, Haochen Liu, Yiqi Wang, Suhang Wang, Zitao Liu, and Jiliang Tang. 2020. Self-supervised Learning on Graphs: Deep Insights and New Direction. (2020). arXiv:2006.10141
- [22] Thomas N. Kipf and Max Welling. 2017. Semi-Supervised Classification with Graph Convolutional Networks. In *Proceedings of the 5th International Conference on Learning Representations, ICLR'17*. France.
- [23] Yehuda Koren, Robert M. Bell, and Chris Volinsky. 2009. Matrix Factorization Techniques for Recommender Systems. *Computer* (2009), 30–37.
- [24] Haoyang Li, Xin Wang, Ziwei Zhang, Zehuan Yuan, Hang Li, and Wenwu Zhu. 2021. Disentangled Contrastive Learning on Graphs. In *NeurIPS*.
- [25] Hui Li, Dingming Wu, Wenbin Tang, and Nikos Mamoulis. 2015. Overlapping community regularization for rating prediction in social recommender systems. In *Proceedings of the 9th ACM Conference on Recommender Systems*. ACM.
- [26] Shuai Lin, Pan Zhou, Zi-Yuan Hu, Shuojia Wang, Ruihui Zhao, Yefeng Zheng, Liang Lin, Eric Xing, and Xiaodan Liang. 2021. Prototypical Graph Contrastive Learning. (2021). arXiv:2106.09645
- [27] Haifeng Liu, Hongfei Lin, Wenqi Fan, Yuqi Ren, Bo Xu, Xiaokun Zhang, Dongzhen Wen, Nan Zhao, Yuan Lin, and Liang Yang. 2022. Self-supervised learning for fair recommender systems. *Applied Soft Computing* (2022), 109126.
- [28] Haifeng Liu, Hongfei Lin, Bo Xu, Liang Yang, Yuan Lin, Yonghe Chu, Wenqi Fan, and Nan Zhao. 2020. Improving social recommendations with item relationships. In *International Conference on Neural Information Processing*. Springer, 763–770.
- [29] Haochen Liu, Yiqi Wang, Wenqi Fan, Xiaorui Liu, Yaxin Li, Shaili Jain, Yunhao Liu, Anil K Jain, and Jiliang Tang. 2021. Trustworthy ai: A computational perspective. *arXiv preprint arXiv:2107.06641* (2021).
- [30] Hao Ma, Michael R. Lyu, and Irwin King. 2009. Learning to recommend with trust and distrust relationships. In *Proceedings of the 3rd ACM Conference on Recommender Systems, RecSys'09*. ACM.
- [31] Hao Ma, Dengyong Zhou, Chao Liu, Michael R. Lyu, and Irwin King. 2011. Recommender systems with social regularization. In *Proceedings of the 23rd ACM International Conference on Conference on Information and Knowledge Management, CIKM'14*. ACM.
- [32] Peter V Marsden and Noah E Friedkin. 1993. Network studies of social influence. *Sociological Methods & Research* 22 (1993), 127–151.
- [33] Miller McPherson, Lynn Smith-Lovin, and James M Cook. 2001. Birds of a feather: Homophily in social networks. *Annual Review of Sociology* 27 (2001), 415–444.
- [34] Steffen Rendle, Christoph Freudenthaler, Zeno Gantner, and Lars Schmidt-Thieme. 2009. BPR: Bayesian personalized ranking from implicit feedback. In *Proceedings of the 25th Conference on Uncertainty in Artificial Intelligence*. 452–461.
- [35] Jiliang Tang, Huiji Gao, Huan Liu, and Atish Das Sarma. 2012. eTrust: understanding trust evolution in an online world. In *The 18th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*.
- [36] Aaron van den Oord, Yazhe Li, and Oriol Vinyals. 2019. Representation Learning with Contrastive Predictive Coding. (2019). arXiv:1807.03748 [cs.LG]
- [37] Tongzhou Wang and Phillip Isola. 2020. Understanding Contrastive Representation Learning through Alignment and Uniformity on the Hypersphere. In *Proceedings of the 37th International Conference on Machine Learning*.
- [38] Xiang Wang, Xiangnan He, Meng Wang, Fuli Feng, and Tat-Seng Chua. 2019. Neural graph collaborative filtering. In *Proceedings of the 42nd international ACM SIGIR conference on Research and development in Information Retrieval*. ACM.
- [39] Jiancan Wu, Xiang Wang, Fuli Feng, Xiangnan He, Liang Chen, Jianxun Lian, and Xing Xie. 2021. Self-supervised graph learning for recommendation. In *Proceedings of the 44th International ACM SIGIR Conference on Research and Development in Information Retrieval, SIGIR'21*. ACM, Virtual Event, 726–735.
- [40] Le Wu, Junwei Li, Peijie Sun, Richang Hong, Yong Ge, and Meng Wang. 2020. DiffNet++: A Neural Influence and Interest Diffusion Network for Social Recommendation. *IEEE Transactions on Knowledge and Data Engineering* (2020).
- [41] Lirong Wu, Haitao Lin, Zhangyang Gao, Cheng Tan, Stan Li, et al. 2021. Self-supervised Learning on Graphs: Contrastive, Generative, or Predictive. *IEEE Transactions on Knowledge and Data Engineering* (2021).
- [42] Le Wu, Peijie Sun, Yanjie Fu, Richang Hong, Xiting Wang, and Meng Wang. 2019. A neural influence diffusion model for social recommendation. In *Proceedings of the 42nd International ACM SIGIR Conference on Research and Development in Information Retrieval, SIGIR'19*. ACM, France, 235–244.
- [43] Qitian Wu, Hengrui Zhang, Xiaofeng Gao, Peng He, Paul Weng, Han Gao, and Guihai Chen. 2019. Dual graph attention networks for deep latent representation of multifaceted social effects in recommender systems. In *WWW*. ACM.
- [44] Yuning You, Tianlong Chen, Yongduo Sui, Ting Chen, Zhangyang Wang, and Yang Shen. 2020. Graph contrastive learning with augmentations. In *NeurIPS*. 5812–5823.
- [45] Junliang Yu, Hongzhi Yin, Min Gao, Xin Xia, Xiangliang Zhang, and Nguyen Quoc Viet Hung. 2021. Socially-aware self-supervised tri-Training for recommendation. In *Proceedings of the 27th ACM SIGKDD Conference on Knowledge Discovery and Data Mining, KDD'21*. ACM, Virtual Event, 2084–2092.
- [46] Junliang Yu, Hongzhi Yin, Jundong Li, Qinyong Wang, Nguyen Quoc Viet Hung, and Xiangliang Zhang. 2021. Self-supervised multi-channel hypergraph convolutional network for social recommendation. In *Proceedings of the 32nd Web Conference WWW'21*. ACM / IW3C2, 413–424.
- [47] Tong Zhao, Julian McAuley, and Irwin King. 2014. Leveraging social connections to improve personalized ranking for collaborative filtering. In *CIKM*. ACM.
- [48] Xiangyu Zhao, Haochen Liu, Wenqi Fan, Hui Liu, Jiliang Tang, and Chong Wang. 2021. Autoloss: Automated loss function search in recommendations. In *Proceedings of the 27th ACM SIGKDD Conference on Knowledge Discovery & Data Mining*.
- [49] Xiangyu Zhaok, Haochen Liu, Wenqi Fan, Hui Liu, Jiliang Tang, Chong Wang, Ming Chen, Xudong Zheng, Xiaobing Liu, and Xiwang Yang. 2021. Autoemb: Automated embedding dimensionality search in streaming recommendations. In *2021 IEEE International Conference on Data Mining (ICDM)*. IEEE.
- [50] Yanqiao Zhu, Yichen Xu, Feng Yu, Qiang Liu, Shu Wu, and Liang Wang. 2021. Graph contrastive learning with adaptive augmentation. In *WWW*. ACM.

5 APPENDIX

5.1 Related Work

In this section, we will review previous work on social recommendation and SSL in recommendation.

5.1.1 GNNs-based Social Recommendations. Recommender systems play an increasing role in various applications in our daily life [1, 8, 48, 49], such as online shopping and social media. It’s a folklore knowledge that users’ preferences and decisions are swayed by those who are socially connected with them [28, 32, 33]. Therefore, it’s intuitive to integrate the social connection information into recommendation modeling. Graph neural networks (GNNs) are emerging in recent years and have achieved promising performances in many tasks [29], as well as recommendation [13]. The intuition of those prevalent GNN-based recommendation models (e.g., NGCF [38] and LightGCN [18]) is to utilize GNN to aggregate neighbors’ information so as to learn the supervisory signals of high-order structure. To be more specific, in the field of social recommendation, GNNs also gained considerable attention. GraphRec [12] is the very first GNN-based social recommendation method by modeling user-item interactions and social connections as graphs. DANSER [43] proposes dual graph attention networks to collaboratively learn representations for two-fold social effects. DiffNet [42] models the recursive dynamic social diffusion in social recommendation with a layer-wise propagation structure. DASO [7] adopts a bidirectional mapping method to transfer users’ information between social domain and item domain using adversarial learning.

5.1.2 Self-Supervised Learning in Recommendations. Self-supervised learning (SSL) is becoming more and more prevalent in recent years, which is utilized to extract supervisory signals from data to learn expressive representations without labels. SSL was first applied in tasks on image data [2, 3, 17], gaining promising performance. Naturally, there are tons of work extending the SSL to graph domain [21, 27, 41]. Since SSL has gained promising performance on graph representation learning, some recent studies also verify that this paradigm also work in the scenario of recommendation. SGL [39] proposes to devise an auxiliary self-supervised task to supplement the classical supervised task, mitigating the problem of imbalanced-degree distribution among nodes and vulnerability to noisy interactions of learned representations. SEPT [45] proposes a socially-aware SSL framework that integrates tri-training to capture supervisory signals that are not only from self, but also from other nodes. MHCN [46] proposes a multi-channel hypergraph convolutional network to enhance social recommendation by leveraging high-order user relations. In [16], authors propose a

pre-training task to simulate the cold-start scenarios from the users/items with sufficient interactions and take the embedding reconstruction as the pretext task, improving the quality of the learned representations.

Despite their excellent performance, they ignore the heterogeneous behavior patterns of users in the scenario of social recommendation. In this work, the proposed framework aims to model this kind of heterogeneity to assist in further boosting recommendations’ performance.

5.2 Datasets

We conduct experiments on two real-world datasets: Dianping [25] and Ciao [35]. Since we aim at producing Top-K recommendations, we leave out the ratings less than 4 and utilize the rest in these two datasets, where users’ ratings for items range from 1 to 5. The statistics of the datasets are shown in Table 3. For each dataset, the ratio of splitting the interactions into training, validation, and testing set is 8 : 1 : 1.

5.3 Baselines and Implementation

We conduct experiments by comparing with various kinds of baselines, including MF-based (BPR [34], SBPR [47], SoRec [31], SocialMF [20]), GNNs-based (Diffnet [42], NGCF [38], and LightGCN [18]), as well as SSL-enhanced recommendation methods (SGL [39], MHCN [46] and SEPT [45]). The baselines LightGCN+Social and SGL+Social are implemented by adding social information into their adjacency matrices for propagation via GNNs techniques in social recommendation tasks. For implementation, BPR, SBPR, SoRec, SocialMF, Diffnet, MHCN, and SEPT are from the open-source library QRec. The rest baselines are implemented based on the implementation of LightGCN [18]. For a fair comparison, we apply grid search to fine-tune the hyperparameters of the baselines, initialized with the optimal parameters reported in the original papers. We use Adam optimizer to optimize all these models.

5.4 Evaluation Metrics

For the metrics, we follow the ranking protocol used in [39] to evaluate the top-K recommendation performance and report the average *NDCG*, *Recall*, and *Precision*, where $K=5$. Higher values of these three metrics indicate better predictive performance.

Table 3: Dataset Statistics

Dataset	#Users	#Items	#Ratings	#Relations	Density
Dianping	16,396	14,546	51,946	95,010	0.022%
Ciao	7,375	105,114	284,086	111,781	0.037%